



TYPICAL SIGN INSTALLATIONS

NOTES:

1. SIGNING DETAILS SHOWN ON THIS SHEET ARE INTENDED TO CONVEY TYPICAL CONDITIONS ONLY. SPECIFIC LOCATIONS MAY REQUIRE INSTALLATIONS DIFFERENT FROM THOSE SHOWN HERE.
2. IF THE MAXIMUM DIMENSION OF A SIGN IS 36" OR LESS, USE A 4"x4" POST. IF THE MAXIMUM DIMENSION EXCEEDS 36", USE A 4"x6" POST. FOR MOUNTING PLYWOOD OR SHEET ALUMINUM SIGNS ON WOODEN POSTS, USE 3/8"x3" GALVANIZED LAG BOLTS WITH STAINLESS STEEL OR NEOPRENE WASHERS.
3. "STOP" SIGNS SHALL ALWAYS BE INSTALLED AT 6.0'-8.0' VERTICAL CLEARANCE.
4. USE 4.0' MINIMUM VERTICAL CLEARANCE ONLY IF SECONDARY SIGN IS 24" OR LESS IN WIDTH.
5. FOR INSTALLATION IN HARD-SURFACED AREAS, ALTERNATIVE POST INSTALLATIONS MAY BE USED WITH APPROVAL OF THE PROJECT ENGINEER.
6. FOR ADDITIONAL INFORMATION REGARDING LOCATION AND INSTALLATION OF SIGNS AND POSTS, CONSULT THE CURRENT MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (M.U.T.C.D.).



CITY of LEBANON SUPPLEMENTAL DRAWING

APPROVED

Donald J. H. ...
CITY ENGINEER

TEMPORARY
(CONSTRUCTION)
SIGNING

DATE:
Jan. 2009

DRAWING NO:
00200-02