



BASE DR	54" & 60"		72"		84"		96"	
DEPTH*	0'-15'	15'-30'	0'-15'	15'-30'	0'-15'	15'-30'	0'-15'	15'-30'
Ts	7.0"	9.0"	7.0"	9.0"	8.0"	10.0"	9.0"	11.0"
E BARS	#4 @ 12"	#4 @ 9"	#4 @ 9"	#4 @ 6"	#4 @ 8"	#5 @ 9"	#4 @ 7"	#5 @ 8"
F BARS	#4 @ 12"	#4 @ 9"	#4 @ 9"	#4 @ 6"	#4 @ 8"	#5 @ 9"	#4 @ 7"	#5 @ 8"

*INVERT TO STREET GRADE

NOTES:

1. 24" MANHOLE ONLY ALLOWED UPON APPROVAL OF THE CITY ENGINEER.
2. ALL CONCRETE SHALL BE COMMERCIAL GRADE CONCRETE.
3. CHANNELS SHALL BE CONSTRUCTED TO PROVIDE SMOOTH SLOPES AND RADII TO OUTLET.
4. PIPE CONNECTIONS SHALL CONFORM TO SECTION 00400.



CITY of LEBANON SUPPLEMENTAL DRAWING

APPROVED

Domalof H. H. H. H.
CITY ENGINEER

LIVE SANITARY
CAST-IN-PLACE
MANHOLE

DATE:
Jan. 2009

DRAWING NO:
00400-28