



- ZONE 1: ONLY CROSSING RESTRICTIONS APPLY
- ZONE 2: CASE-BY-CASE DETERMINATION
- ZONE 3: PARALLEL WATER LINE PROHIBITED
- ZONE 4: PARALLEL WATER LINE PROHIBITED

ATTENTION:
VERTICAL AND HORIZONTAL SEPARATION DISTANCES ARE CONTROLLED BY THE DEPARTMENT OF ENVIRONMENTAL QUALITY, DEPARTMENT OF COMMERCE, STATE HEALTH DIVISION, AND LOCAL UTILITY COMPANIES.

WATER LINE-SEWER LINE SEPARATION
(AS REQUIRED BY OAR 333-061-0050)

NOTES:

1. MANHOLES SHALL NOT BE INSTALLED IN VEHICLE WHEEL PATHS.
2. A 4' MINIMUM COVER IS REQUIRED FOR DISTRIBUTION FACILITIES TO CROSS OVER PIPE.
3. SEWER MAINS SHALL BE LOCATED UNDER PAVED AREAS.
4. ISSUES CONCERNING VAULTS, HYDRANTS, CATCH BASINS, PEDESTALS, MAILBOXES, ETC. SHALL BE RESOLVED WITH THE INVOLVED UTILITIES PRIOR TO CONSTRUCTION.
5. RECOMMENDED FOR RIGHTS-OF-WAY LESS THAN 60'.
6. LATERALS ARE TO BE INSTALLED FROM THE SANITARY SEWER MAIN TO RIGHT-OF-WAY DURING INITIAL CONSTRUCTION. SEE SUPP. DWG. 00400-02 FOR SERVICE LATERAL MARKER DETAILS.
7. WATER AND GAS UTILITIES SHALL BE INSTALLED ON OPPOSITE SIDES OF THE RIGHT-OF-WAY.
8. PLACEMENT OF SIDEWALK AGAINST THE CURB WILL ONLY BE ALLOWED WITH APPROVAL OF THE CITY ENGINEER.



CITY of LEBANON SUPPLEMENTAL DRAWING

APPROVED

Doreen J. Haanick
CITY ENGINEER

TYPICAL UTILITY LOCATIONS

DATE:
Jan. 2009

DRAWING NO:
00300-02